



A 65 Browns Dip Road
Enoggera Qld 4051 Australia
T +61 7 3855 3909
F +61 7 3251 0584
ABN 39 083 322 141

PRODUCT PROFILE



GARDEX

Hot Melt Anti-Adhesion Compound

Description

GARDEX hot melt release agent is a unique formulation developed to benefit any industry that uses hot melt adhesive. The unwanted build-up of hot melt is a common problem leading to machine downtime and therefore loss of production.

Temperature stable up to 220°C.

GARDEX is available in 5kg and 1kg.

Areas of Application

GARDEX can be used to coat the inside of all hot melt glue pots on edge banders and all melt tanks within a hot melt glue system. Also used to protect daubers, drive chains, drive shafts, screw threads, temperature probes, universal joints etc.

Packaging Industry

Use **GARDEX** on all areas around the glue systems including pots, nozzles, modules, hoses, chains, drainage points etc.

Woodworking Industry

Apply **GARDEX** to all edge banders and associated equipment.

Benefits

Economical

Only a fine coating of **GARDEX** is required to treat areas.
Treated glue pots stay protected for up to six months.

A little goes a long way!

Easy to Use

Simply apply **GARDEX** with a clean cloth or sponge to all areas that become contaminated with hot melt. (Note: do not apply to guide rails/belts etc).
Easy to follow instructions are on every pack.



Nonfood Compounds
Program Listed (H1)
148386