

A 65 Browns Dip Road Enoggera Qld 4051 Australia T +61 7 3855 3909 F +61 7 3251 0584 ABN 39 083 322 141

## Product **Profile**



GARDOL® Adhesive / Glue / Latex Shield FDA Approved 175.105



## Description

GARDOL® prevents the unwanted build-up of cold adhesive and glues on machinery / equipment.

**GARDOL**® is a unique product development which will improve work flow and save valuable down time.

**GARDOL®** is available in 5kg containers.

Protects Against • Casein • P.V.A. • Phenol • Urea	<ul><li>Polyurethane</li><li>Melamine</li><li>Starch</li><li>Polysulphide</li></ul>	<ul> <li>Epoxy</li> <li>Resorcinal</li> <li>Polyester</li> <li>Vinyl</li> </ul>
Where Gardol® is Used Packaging	Apply <b>GARDOL®</b> to glue pots, drive shafts, areas of overspray, doctor blade assemblies, cylinder journals, application trays, cylinder shafts, holding tanks etc	
<u>Bottling</u>	Apply <b>GARDOL®</b> to shafts, turntables, lable fingers, plastic guards, return chutes etc. Always re-apply after washing down. (Note – do not apply to pallets)	
Carpet Backing	Apply GARDOL® to doctor blades, roller ends, latex tanks, drip trays etc	
<u>Woodworking</u>	Apply <b>GARDOL®</b> to pressing equipment, form press, press band, press roller and application equipment. Platens should be coated 2-3 times a day using a cloth. If particularly high temperatures are used, repeat the process more often. ( <b>GARDOL®</b> contains no silicones.)	
Benefits Economical	Only a fine coating of GARDOL® is required to treat areas. Treated areas stay protected until washed clean. A little goes a long way!	
Easy to Use	Simply apply <b>GARDOL</b> ® with a clean cloth or sponge to all areas that become contaminated with adhesive. Easy to follow instructions are on every pack.	